LUXMETER ENERGY

HI CLEAN

- ✓ Luminous efficiency 140LM/W.
- ✓ IP Rating IP66.
- ✓ Protection index IK10.
- ✓ Self-cleaning
- ✓ Covered by high transmittance PC instead of glass.
- ✓ Led power 100W to 200W

Intelligent control

DALI Control
Microwave Sensor
Zigbee Wireless Control

Accessory

Pc cover	H25201 / H00B04
Bracket	Surface mount bracket
PC Optics Lens	H25203, H25202 and H25201
Safety Chain	250mm chain, M10 + M10 Hook>340mm

ELECTRICAL DETAILS

MODEL	HB06-150
POWER CONSUMPTION	150 ± 7W
LED TYPE	SMD
LUMINOUS FLUX (± 5%)	21000lm
EFFICACY (5000K Ra70)	140lm / W
CORRELATED COLOR TEMPERATURE	5000K (3000K 4000K optional)
COLOR RENDERING INDEX	Ra70 (Ra80 opcional)
INPUT VOLTAJE	100-240 VCA 100-277 VCA
POWER FACTOR	> 0.92
FREQUENCY	50/60Hz
DRIVER TYPE	Constant current (CC)
SURGE PROTETION	2kV line-line 4kV line-earth
BEAM ANGLE	H00A02, H00B03, H00B04 H25201, H25202, H25203

TECHNICAL DETAILS

PRODUCT DIMENSION	φ489 × 200 mm (φ19.25 "x 7.87")
LUMINAIRE NET WEIGHT	7.2 ± 0.3kg (15.87 ± 0.66Lbs)
GROSS WEIGHT	9.3 ± 0.3 kg (20.4 ± 0.66 lb)
FINISH	Powder Coating
FIXTURE COLOR	Grey / White
IP RATING	IP66
WARRANTY	2 yeas
DIMMABLE	Dimmable and non-dimmable
OPERATING TEMPERATURE	- 30 ° C to +50 ° C (-22 ° F to 122 ° F)
MOUNTING OPTION	Loop Hanging / Ceiling Mounting, Pipe Mouting

H00005



H25201



H25202